

2. Models and Modelling

Angelo Gargantini

Testing e Verifica del Software AA 2526

February 24, 2026

- From wind-tunnels to Navier-Stokes equations to circuit diagrams to finite-element models of buildings, engineers in all fields of engineering construct and analyze models.
- Several advantages:
 - ① analysis and test can be performed before the actual artifact is constructed,
 - ② Models permit us to start analysis earlier and repeat it as a design evolves, and allows us to apply analytic methods that cover a much larger class of scenarios than we can explicitly test.
 - ③ Importantly, many of these analyses may be automated.

Compact A model must be representable and manipulable in a reasonably **compact** form. Models intended for human inspection and reasoning must be small enough to be comprehensible. Models intended solely for automated analysis may be far too large and complex for human comprehension, but must still be sufficiently small or regular for computer processing.

Predictive A model used in analysis or design must represent some salient characteristics of the modeled artifact well enough to distinguish between “good” and “bad” outcomes of analysis, with respect to those characteristics.

Multiple models Typically, no single model represents all characteristics well enough to be useful for all kinds of analysis. One does not, for example, use the same model to predict airflow over an aircraft fuselage and to design internal layout for efficient passenger loading and safe emergency exit.

Semantically meaningful Beyond distinguishing between predictions of success and failure, it is usually necessary to interpret analysis results in a way that permits diagnosis of the causes of failure. If a finite-element model of a building predicts collapse in a category five hurricane, we want to know enough about that collapse to suggest revisions to the design. Likewise, if a model of an accounting system predicts a failure when used concurrently by several clients, we need a description of that failure sufficient to suggest possible revisions.

Sufficiently general Models intended for analysis of some important characteristic (e.g., withstanding earthquakes or concurrent operation by many clients) must be general enough for practical use in the intended domain of application.

How to model your system

- Focus primarily on the SUT
- Show only those classes (or subsystems) associated with the SUT and whose values will be needed in the test data
- Include only those operations that you wish to test
- Include only the data fields that are useful for modeling the behavior of the operations that will be tested
- Replace a complex data field, or a class, by a simple enumeration. This allows you to limit the test data to several carefully chosen example values (one for each value of the enumeration).

- Pre/post (or state-based) notations
- Transition-based notations
- History-based notations
- Functional notation
- Operational notations
- Statistical notations

Choosing a Notation

- 1 Pre/post notations are best for data-oriented systems. Transition-based notations are best for control-oriented systems.
- 2 Model-based testing requires an accurate model, written in a formal modeling notation that has precise semantics.
- 3 **two main families**: *operational* (also called “imperative”) and *declarative*. An operational modeller asks “how would I make X happen?”. A declarative modeller asks “how would I recognize that X has happened?”. In many contexts, it is more natural and concise to use a declarative description. Often one need only to describe the rules of the game and what it means to have won, and not even think about what moves will be needed (and which must be avoided) in order to win.

Declarative vs operational notations

Le notazioni operazionali e dichiarative sono due approcci distinti nel descrivere come funzionano i sistemi o come devono essere eseguite le operazioni, ma si differenziano principalmente nel modo in cui vengono espresse le informazioni.

- La notazione operazionale si concentra sul **come** vengono eseguite le operazioni.
- La notazione dichiarativa, invece, si concentra sul **cosa** deve essere fatto, senza entrare nei dettagli di **come** farlo.

Esempio: calcolo del massimo in un array

come scriveresti il massimo di un array in modo dichiarativo ed operativo?

guarda i lucidi 2_1_model_with_FSM.pdf

- 1 Mealy/Moore FSM
- 2 Kripke Structure

guarda i lucidi

